
Submitted Model No.:

Specific Features:



▲ Designate proper finish suffix

Brizo reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.brizo.com for finish options and product availability.

BRIZO **HYDRATI®** 2|1 SHOWER

FEATURES:

- H₂Okinetic® Technology
- MagnaDock® Technology

STANDARD SPECIFICATIONS:

- Maximum 2.5 gpm @ 80 psi, 9.5 L/min @ 550 kPa (86200-2.5, 86201-2.5, 86275-2.5, 86280-2.5)
- Maximum 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa (86201, 86280, 86220)
- Showerhead and handshower all in one
- 3-way diverter showerhead only, handshower only, and combo
- Integrated handshower docks securely into showerhead with MagneDock[®] technology
 Four-setting push button handshower
- 60" (1524 mm) stretchable finished metal hose stretches to 82" (2083 mm) for extra reach

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1 ◆
- EPA WaterSense®
- Your Brizo Faucet handshower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, nonserviceable parts of the wand assembly.

Brizo Kitchen & Bath Company

55 E. 111th Street, Indianapolis, Indiana 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2017 Brizo Kitchen & Bath Company