

### Rain shower for surface-mounted ceiling installation 300 mm

#### 28 031 970



- rain shower Ø 300 mm
- Rain flow, max. flow rate 6,8 l/min
  Spray flow, max. flow rate 6,8 l/min
- Spray now, max. now rate 6,8 /min
  Distance to ceiling from bottom edge of shower 40
- mm
- with anti-scale system
- Not suitable for use in a steam bath
- For simultaneous control of the jet types, we
- recommend the xTool thermostat module
  This product can help a building to meet

10	Chrome	28 031 970-00 0010
	Brushed Platinum	28 031 970-06 0010
	Platinum	28 031 970-08 0010
	Matte White	28 031 970-10 0010
at	Brushed Durabrass (23kt Gold)	28 031 970-28 0010
	Matte Black	28 031 970-33 0010
	Brushed Champagne (22kt Gold)	28 031 970-46 0010
S	Champagne (22kt Gold)	28 031 970-47 0010
	Brushed Chrome	28 031 970-93 0010
	Brushed Dark Platinum	28 031 970-99 0010

 This product call negative a building Rating Systems, e.g. LEED®, BREEAM®, DGNB, WELL
 Three-way diverter ensures that the product does not exceed the max. flow rate of 2.5 gpm any setting. It does not permit the use of two functions simultaneously.
 Three-way diverter trim is sold separately
 Three-way diverter ensures that the product does

Three-way diverter ensures that the product does not exceed the max. flow rate of 2.5 gpm at any setting. It does not permit the use of two functions simultaneously.

Three-way diverter trim is sold separately

#### Required miscellaneous



Concealed ceiling installation box35 041 970-90for surface-mounted ceiling0010installation•min. recess depth 90 mm


•max. recess depth 90 mm




# Rain shower for surface-mounted ceiling installation 300 mm


#### 28 031 970

mm [inches]





### Flow rate chart



# Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	90 17 20 263 00 90	fixing set	1	30
2	90 24 03 309 02 90	connection	2	2