

Body spray without volume control FlowReduce

28 518 979



- spray head Ø 55mm
- ball-joint pivotable through 25° (in any direction)
- rain flow
- with anti-scale system
- rosette Ø 55 mm
- 1/2" connection
- max. flow 5 l/min

Codes & standards

- This product can help a building to meet requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB, WELL

	Chrome	28 518 979-00
	Brushed Platinum	28 518 979-06
	Platinum	28 518 979-08
	Durabrand (23kt Gold)	28 518 979-09
	Dark Chrome	28 518 979-19
	Brushed Durabrand (23kt Gold)	28 518 979-28
	Matte Black	28 518 979-33
	Brushed Champagne (22kt Gold)	28 518 979-46
	Champagne (22kt Gold)	28 518 979-47
	Brushed Chrome	28 518 979-93
	Brushed Dark Platinum	28 518 979-99

Required miscellaneous

Concealed adapter


35 080 970-90
0010




Body spray without volume control FlowReduce

28 518 979

mm [inches]



Flow rate chart




Codes & Standards

ASME	California Energy
A112.18.1/CSA	Commission
B125.1	(CEC)

Body spray without volume control FlowReduce

28 518 979



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	09 14 10 026 90	seal	1	2
2	09 27 22 003-00	rosette	1	10
3	09 23 30 026-00	nut	1	10
4	09 14 15 010 90	ring	1	2
5	09 16 01 014 90	ring	1	2
6	09 23 01 048 90	back-flow preventer	1	2
7	09 21 40 016-00	connection	1	10
8	09 14 10 015 90	seal	1	2
9	90 12 05 027 00-00	casing (completely)	1	10