



# Highline® | K-26813

One-piece elongated toilet, 1.28 gpf

## Features

- One-piece toilets integrate the tank and bowl into a seamless, easy-to-clean design
- Elongated bowl offers added room and comfort
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults
- 1.28 gpf (4.8 lpf)
- Left-hand Polished Chrome trip lever
- 2-1/8" (54 mm) fully glazed trapway
- Quiet-Close® lid and seat prevents slamming
- Grip-Tight bumpers hold seat firmly in place
- Precision-engineered tank, bowl, and trapway create strong siphon during flushing
- Class Five® canister optimizes the flow out of the tank, harnessing gravity and the natural, powerful reducing cascade of water to increase the power and effectiveness of the flush
- Easy-to-flush canister design requires less force to actuate than a 3" (76 mm) flapper, and has 90% less exposed seal material which resists conditions that cause wear, tear, shrinkage and swelling



## Sustainability



## Available Colors/Finishes

*Color tiles intended for reference only.*

- 0 White



1-800-4KOHLER (1-800-456-4537)  
Kohler Co. reserves the right to make revisions without notice to product specifications.  
For the most current specification sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada.  
4-15-2026 6:40 - US-CA

THE BOLD LOOK  
OF **KOHLER**®

## Codes/Standards

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Accessibility standards may require controls to be located on the open side of the toilet.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.



ASME A112.19.2/CSA B45.1  
DOE - Energy Policy Act 1992  
EPA WaterSense®  
California Energy Commission (CEC)  
ADA  
ICC/ANSI A117.1  
CSA B651  
OBC

## Technical Information

|                       |                                   |
|-----------------------|-----------------------------------|
| Rough-in:             | Standard 12" (305mm)              |
| Flush Type:           | AquaPiston, Class Five            |
| Flush Rate:           | 1.28 gpf (4.8 lpf)                |
| Bowl Shape:           | Elongated                         |
| Seat-Mounting Holes:  | 5-1/2" (140 mm)                   |
| Waste Outlet:         | Floor                             |
| Trapway Size:         | 1-15/16" (49 mm)                  |
| Trapway Type:         | Exposed                           |
| Water Surface Size:   | 9-5/8" x 7-1/4" (245 mm x 184 mm) |
| Rim to Water Surface: | 6-1/2" (165 mm)                   |

## Pressure/Fixture Supply Requirements

|                    |                   |
|--------------------|-------------------|
| Minimum Flow Rate: | 1 gpm (3.8 l/min) |
|--------------------|-------------------|

## Warranty

See website for detailed warranty information.

KOHLER® Toilets and Seats Limited Warranty



1-800-4KOHLER (1-800-456-4537)  
Kohler Co. reserves the right to make revisions without notice to product specifications.  
For the most current specification sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada.  
4-15-2026 6:40 - US-CA

