

## Wellworth® Classic | K-3531-TR

Two-piece elongated toilet, 1.0 gpf

### Features

- Elongated bowl offers added room and comfort
- Equipped with Sloan FLUSHMATE® – Sloan® Valve Company
- Polished Chrome trip lever
- Tank cover locks included
- 1.0 gpf (3.8 lpf)



### Sustainability



### Available Colors/Finishes

*Color tiles intended for reference only.*

■ 0 White



## Codes/Standards

*Accessibility standards may require controls to be located on the open side of the toilet.*

*Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.*

*This product should be used with a WaterSense labeled counterpart with the same rated flush volume to ensure the complete system meets the requirements of this specification for water efficiency and performance.*



ASME A112.19.2/CSA B45.1  
DOE - Energy Policy Act 1992  
EPA WaterSense®  
California Energy Commission (CEC)

## Warranty

See website for detailed warranty information.

KOHLER® One-Year Limited Warranty

## Technical Information

Installation Type:	Floor-mount
Rough-in:	Standard 12" (305mm)
Flush Type:	Pressure Lite
Flush Rate:	1.0 gpf (3.8 lpf)
Bowl Shape:	Elongated
Seat-Mounting Holes:	5-1/2" (140 mm)
Waste Outlet:	Floor
Trapway Size:	2-1/4" (57 mm)
Trapway Type:	Exposed
Water Surface Size:	11-1/2" x 9-1/2" (292 mm x 241 mm)
Rim to Water Surface:	5-5/8" (143 mm)

## Included Combo Skus

- K-4303 Elongated toilet bowl
- K-4484-TR Toilet tank, 1.0 gpf

## Recommended Products/Accessories

- K-5588 Deodorizing elongated toilet seat
- K-5420 Low-profile toilet bolt caps
- K-4108 Elongated bidet toilet seat with remote control



1-800-4KOHLER (1-800-456-4537)  
Kohler Co. reserves the right to make revisions without notice to product specifications.  
For the most current specification sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada.  
4-15-2026 8:0 - US-CA

## Installation

- Seat and supply line sold separately
  - Standard 12" (305 mm) rough-in
- 

## Installation Notes

*Install this product according to the installation instructions.*

For back-to-back toilet installations: Use only a 45° double wye fitting.

Product dimensions are nominal and may vary per ASME A112.19.2 tolerances.

