



Highline® | K-35704

Elongated toilet bowl

Features

- Elongated bowl offers added room and comfort
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults
- 2" (51 mm) fully glazed trapway
- Combines with either the K-44471 or K-44471-RA tank
- Revolution 360® flushing technology generates a forceful swirling motion to keep the bowl clean longer
- Weighs less than previous Highline models
- Replaces Highline® K-5297 bowl



Available Colors/Finishes

Color tiles intended for reference only.

	0	White
	96	Biscuit
	7	Black Black



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.

6-29-2026 21:9 - US-CA

THE BOLD LOOK
OF **KOHLER**®

Codes/Standards

Accessibility standards may require controls to be located on the open side of the toilet.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

ASME A112.19.2/CSA B45.1

Technical Information

Rough-in:	Standard 12" (305mm)
Flush Type:	AquaPiston
Bowl Shape:	Elongated
Seat-Mounting Holes:	5-1/2" (140 mm)
Waste Outlet:	Floor
Trapway Size:	2-1/8" (54 mm)
Trapway Type:	Exposed
Water Surface Size:	8" x 8" (203 mm x 203 mm)
Rim to Water Surface:	7-1/16" (179 mm)

Recommended Products/Accessories

K-44471 Toilet tank, 1.0 gpf

K-44471-RA Toilet tank, 1.0 gpf

K-9379 Trip lever

Warranty

See website for detailed warranty information.

KOHLER® Toilets and Seats Limited Warranty



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.

6-29-2026 21:9 - US-CA

No image available.

This product is a component and not intended to be a standalone installation.

Installation

- Standard 12" (305 mm) rough-in
-

Installation Notes

Install this product according to the installation instructions.

