

# **NADYA**

#### **Features**

- Solid brass construction
- Quarter-turn washerless ceramic disc valve cartridges
- · Spout assembly with integral supply hoses
- · Spring-loaded, normally closed lever handle
- 6-7/16" (16.4 cm) spout height at outlet
- 4-13/16" (12.2 cm) spout reach (c-c)
- 1.5 gallons (5.7 liters) per minute maximum flow rate
- For single hole configurations



Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- IPC
- NSF 61
- Energy Policy Act of 1992
- All applicable US Federal and State material regulations

## **Hot and Cold Water Dispenser Faucet**

**107** 





#### **Colors / Finishes**

10B: Oil Rubbed Bronze
15: Polished Nickel
15A: Antique Nickel
26: Polished Chrome

 Other: Refer to the Newport Brass catalog for additional color/finish options.

### **Colors / Finishes**

Specified Model		
Model	Description	Colors   Finishes
107	Hot and Cold Water Dispenser Faucet	☐ 10B ☐ 15 ☐ 15A ☐ 26 ☐ Other
5-036	Point-of-Use Water Heater (115V, 140iF to 190i range)	

#### Product Specification: Add "Color / Finish" suffix to Model number, below.

The Hot and Cold Water Dispenser Faucet shall be made of solid brass construction. Faucet shall incorporate a spout assembly with integral supply hoses and feature quarter-turn washerless ceramic disc valve cartridges. Faucet shall incorporate contemporary lever handles and feature a spring-loaded, normally closed hot lever mechanism. Hot and Cold Water Dispenser Faucet shall have a 1.5 gallons (5.7 liters) per minute maximum flow rate and accommodate single hole configurations. Product shall incorporate a 6-7/16" (16.4 cm) spout height at outlet and a 4-13/16" (12.2 cm) spout reach (c-c). Hot and Cold Water Dispenser Faucet shall be Newport Brass Model 107/\_\_\_\_\_. [Point-of-Use Water Heater shall be Newport Brass Model 5-036].

# **107**

## Product Dimensions (units are in inches)



