

ASTAIRE

Features

- · Solid brass construction
- Forged brass body with integral spout and handles
- Quarter-turn washerless ceramic disc valve cartridges
- ADA compliant traditional lever handles
- Spout assembly with integral supply hoses
- 3-3/4" (9.5 cm) spout height at outlet
- 6-7/16" (16.4 cm) spout reach (c-c)
- For 8" (20.3 cm) centers Maximum 20" (50.8 cm)
- 1.5 gallons (5.7 liters) per minute maximum flow rate

Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- IPC
- NSF 61
- ADA
- ICC/ANSI A117.1
- Energy Policy Act of 1992
- All applicable US Federal and State material regulations
- EPA Watersense


Two-Handle Prep Sink / Bar Faucet

1668









Colors / Finishes

10B: Oil Rubbed Bronze
15: Polished Nickel
15A: Antique Nickel
26: Polished Chrome

• Other: Other: Refer to the Newport Brass catalog for additional color/finish options.

Specified Model Model Description Colors / Finishes 1668 Two-Handle Prep Sink / Bar Faucet 10B 15 15A 26 Other

Product Specification:

Add "Color / Finish" suffix to Model number, below.

Faucet shall incorporate a spout assembly with integral supply hoses and feature brass valve bodies with quarter-turn washerless ceramic disc valve cartridges. Faucet shall have a 1.5 gallon (5.7 liter) per minute maximum flow rate. Product shall be for 8" (20.3 cm) centers - Maximum 20" (50.8 cm). Product shall incorporate a 3-3/4" (9.5 cm) spout height at outlet and a 6-7/16" (16.4 cm) spout reach (c-c). Faucet shall incorporate ADA compliant traditional lever handles. Prep Sink / Bar Faucet shall be Newport Brass Model 1668/____.

1668

Product Dimensions (units are in inches)

