

JACOBEAN

Hot Water Dispenser Faucet

2470-5613





Features

- Solid brass construction
- Quarter-turn washerless ceramic disc valve cartridge
- ■Traditional lever handle design
- Spout assembly with integral supply hoses
- Spring-loaded, normally closed lever handle
- 6-5/8" (16.8 cm) spout height at outlet
- **4-3/4**" (12.1 cm) spout reach (c-c)
- ■1.5 gallons (5.7 liters) per minute maximum flow rate
- ■For single hole configurations

Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

- MASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- IPC
- ■NSF 61
- Energy Policy Act of 1992
- ■All applicable US Federal and State material regulations

Colors / Finishes

10B: Oil Rubbed Bronze
15: Polished Nickel
15A: Antique Nickel
26: Polished Chrome

 Other: Refer to the Newport Brass catalog for additional color/finish options.

Specified Model		
Model	Description	Colors / Finishes
2470-5613	Hot Water Dispenser Faucet	☐ 10B ☐ 15 ☐ 15A ☐ 26 ☐ Other
5-036	Point-of-Use Water Heater (115V, 140iF to 190i range)	

Product Specification: Add "Color / Finish" suffix to Model number, below.

The Hot Water Dispenser Faucet shall be made of solid brass construction. Faucet shall incorporate a spout assembly with integral supply hoses and feature a quarter-turn washerless ceramic disc valve cartridge. Faucet shall incorporate a traditional lever handle design and feature a spring-loaded, normally closed hot lever mechanism. Hot Water Dispenser Faucet shall have a 1.5 gallons (5.7 liters) per minute maximum flow rate and accommodate single hole configurations. Product shall incorporate a 6-5/8" (16.8 cm) spout height at outlet and a 4-3/4" (12.1 cm) spout reach (c-c). Hot Water Dispenser Faucet shall be Newport Brass Model 2470-5613/______ . [Point-of-Use Water Heater shall be Newport Brass Model 5-036].

2470-5603

Product Dimensions (units are in inches)



