

VICTORIA

Features

- · Solid brass construction
- ADA compliant traditional lever handles
- 7-3/16" (20.8 cm) spout length
- 1/2" NPT spout inlet quick-connect fitting
- Intended for use with Newport Brass rough valve as specified (Required Accessory)
- Rough valve incorporates a brass valve body assembly
- Rough valve incorporates quarter-turn washerless ceramic disc valve cartridges

Wall-Mounted Tub Trim 3-1775









Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

• ASME A112.18.1/CSA B125.1

Specified Model

- IAPMO/cUPC
- IPC
- ADA
- ICC/ANSI A117.1
- All applicable US Federal and State material regulations

Polished Nickel • 15A: Antique Nickel • 26: Polished Chrome • 10B: Oil Rubbed Bronze

• Other: Refer to the Newport Brass catalog for additional color/finish options.

Colors / Finishes

Model	Description				Colors / Finishes		
3-1775	Wall-I	Vall-Mounted Tub Trim			□ 15 □ 15A □ 26 □ 10B □ Other		
Required Accessory: Both trim, above, and rough valve, below, must be specified.							
Application		Tub Only Valve*	Wall Lavatory Valve	Tub Or	nly Valve*	Wall Lavatory Val	ve
Description	otion 2-Cartridge Assembly with		16pt Spline 2-Car		tridge Assembly with 20pt Spline		
Inlet/Outlet Size		1/2"	1/2"	1/2"		1/2"	
Part Number		1-500	1-532	_ 1-	564	1-560	
Image							

Product Specification:

The Wall-Mounted Tub Trim shall be made of solid brass construction. Wall-Mounted Tub Trim shall include ADA compliant lever handles and a 7-3/16" (20.8 cm) tub spout that incorporates a 1/2" NPT inlet quick-connect fitting. Wall-Mounted Tub Trim shall be Newport Brass Model 3-1775/ and Newport Brass rough valve shall be 1-500.

^{*} Plumbing code restrictions prohibit the use of the 1-500 for showers unless the 1-535 (Remote BP Valve) is installed upstream of the 1-500.

3-1775

Product Dimensions (units are in inches)

MOTES: 1. CUT ALL - THREAD 1/2" SHORTER THAN STEM.

