

# **AYLESBURY**

#### **Features**

- · Solid brass construction
- ADA compliant traditional lever handles
- 7-13/16" (19.8 cm) spout length
- 1/2" NPT spout inlet fitting
- Intended for use with Newport Brass rough valve as specified (Required Accessory)
- Rough valve incorporates a brass valve body assembly
- Rough valve incorporates quarter-turn washerless ceramic disc valve cartridges

# Wall-Mounted Tub Trim **3-2415**










### **Codes / Standards Compliance**

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- IPC
- ADA
- ICC/ANSI A117.1
- All applicable US Federal and State material regulations



#### **Colors / Finishes**

15: Polished Nickel15A: Antique Nickel26: Polished Chrome10B: Oil Rubbed Bronze

• Other: Refer to the Newport Brass catalog for additional color/finish options.

Specified Model							
Model	Description		Colors / Finishes				
3-2415	Wall-Mounted Tub Trim		□ 15 □ 15A □ 26 □ 10B	Other			
Required Accessory:		Both trim, above, and rough valve, below, must be specified.					

Required Ac	ccessory:	Both trim, above, and rough valve, below, must be specified.			
Application	Tub Only Valve*	Wall Lavatory Valve	Tub Only Valve*	Wall Lavatory Valve	
Description	2-Cartridge Assembly with 16pt Spline		oline 2-Cartridge Assembly with 20pt Spline		
Inlet/Outlet Size	1/2"	1/2"	1/2"	1/2"	
Part Number	1-500	1-532	1-564	1-560	
Image					

## **Product Specification:**

The Wall-Mounted Tub Trim shall be made of solid brass construction. Wall-Mounted Tub Trim shall include ADA compliant lever handles and a 7-13/16" (19.8 cm) tub spout that incorporates a 1/2" NPT inlet fitting. Wall-Mounted Tub Trim shall be Newport Brass Model 3-2415/\_\_\_ and Newport Brass rough valve shall be 1-500.

<sup>\*</sup> Plumbing code restrictions prohibit the use of the 1-500 for showers unless the 1-535 (Remote BP Valve) is installed upstream of the 1-500.

# 3-2415

## **Product Dimensions** (units are in inches)

