

ALVESTON

Features

- · Solid brass construction
- ADA compliant traditional cross handles
- 7-9/16" (19.2 cm) spout length
- 1/2" NPT spout inlet fitting
- Intended for use with Newport Brass rough valve as specified (Required Accessory)
- Rough valve incorporates a brass valve body assembly
- Rough valve incorporates quarter-turn washerless ceramic disc valve cartridges




Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- IPC
- ADA
- ICC/ANSI A117.1
- All applicable US Federal and State material regulations

Wall-Mounted Tub Trim 3-925







Colors / Finishes

Polished Nickel 15: • 15A: Antique Nickel • 26: Polished Chrome • 10B: Oil Rubbed Bronze

• Other: Refer to the Newport Brass catalog for additional color/finish options.

Specified Model						
Model	Description			Colors / Finishes		
3-925	Wall-	ll-Mounted Tub Trim			☐ 15 ☐ 15A ☐ 26 ☐ 10B ☐ Other	
Required Accessory: Both trim, above, and rough valve, below, must be specified.						
Application		Tub Only Valve*	Wall Lavatory Valve	Tub Only Valve*		Wall Lavatory Valve
Description		2-Cartridge Assembly with 16pt Spline 2-Ca		2-Cart	tridge Assembly with 20pt Spline	
Inlet/Outlet Size		1/2"	1/2"	1/2"		1/2"
Part Number		1-500	1-532	1-564		1-560
Image		SOC.				

Product Specification:

The Wall-Mounted Tub Trim shall be made of solid brass construction. Wall-Mounted Tub Trim shall include ADA compliant cross handles and a 7-9/16" (19.2 cm) tub spout that incorporates a 1/2" NPT inlet fitting. Wall-Mounted Tub Trim shall be Newport Brass Model 3-925/_ and Newport Brass rough valve shall be 1-500.

^{*} Plumbing code restrictions prohibit the use of the 1-500 for showers unless the 1-535 (Remote BP Valve) is installed upstream of the 1-500.

3-925

Product Dimensions (units are in inches)

