

#### **TAFT**

#### **Features**

- Solid brass construction
- Brass valve bodies
- Quarter-turn washerless ceramic disc valve cartridges
- Two-valve, inlet/outlet flow control design
- ADA compliant contemporary lever handles
- Double-pivot spout with aerated flow
- 4-3/8" (11.1 cm) spout height from wall inlet center
- 21-3/8" (54.3 cm) pivoting spout reach from inlet valve (c-c)
- 3-9/16" (9.0 cm) pivoting inlet valve offset (wall-center)
- For single hole, wall-mounted configurations

## Pot-Filler Faucet **2940-5503**







#### **Codes / Standards Compliance**

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- NSF 61
- NSF 372
- ADA
- ICC/ANSI A117.1
- $\bullet$  All applicable US Federal and State material regulations

#### **Colors / Finishes**

10B: Oil Rubbed Bronze15: Polished Nickel15S: Satin Nickel - PVD

• 26: Polished Chrome

Other: Refer to the Newport Brass

catalog for additional color/finish options.

# Specified Model Model Description Colors | Finishes 2940-5503 Wall-Mounted Pot-Filler Faucet 10B 15 15S 26 Other

#### Product Specification Add "Color / Finish" suffix to Model number, below.

The Pot-Filler Faucet shall be made of solid brass construction. Faucet shall incorporate a double-pivot spout with aerated flow and a feature brass valve bodies with quarter-turn washerless ceramic disc valve cartridges. Pot-filler Faucet shall be a two-valve, inlet/outlet flow control design accommodating single-hole, wall-mounted configurations. Product shall incorporate a 4-3/8" (11.1 cm) spout height from wall inlet center and a 21-3/8" (54.3 cm) pivoting spout reach from inlet valve (c-c). Pot-Filler Faucet pivot axis (inlet valve center) offset shall be 3-9/16" (9.0 cm) (wall-center). Faucet shall incorporate ADA compliant contemporary lever handles. Pot-Filler Faucet shall be Newport Brass Model 2940-5503/\_\_\_\_\_.

### 2940-5503

#### **PRODUCT DIMENSIONS** (Units are in inches)

