

# TOTO®

# MW4483446CEMFGN

## Aquia® IV Arc® WASHLET®+ S5 Two-Piece Toilet - 1.28 GPF/0.9 GPF

### FEATURES

- Concealed supply connection for seamless installation
- DYNAMAX TORNADO FLUSH® utilizes 360° cleaning power to reach every part of the bowl
- Ultra high-efficiency dual flush 1.28 GPF/0.9 GPF (4.8 LPF/3.4 LPF)
- CEFIONTECT® ceramic glaze minimizes waste from sticking to porous ceramic surfaces
- Completely skirted design for a sleek and understated look that's easier to clean
- UNIVERSAL HEIGHT
- Chrome plated trip lever
- 12" Rough-in
- Elongated front bowl toilet and tank with WASHLET+ S5 set
- EWATER+® auto-cleans wand after every use
- PREMIST® automatically mists the bowl before each use
- Self-cleaning wand cleans itself inside and out before and after every use
- CLEAN RESIN® keeps wand and seat cleaner, more hygienic, and effortless to maintain
- Multifunction remote control with personalized memory settings for up to 4 users
- Night light illuminates the inside of the bowl

### MODELS

- **MW4483446CEMFGN (#01)**  
With CEFIONTECT ceramic glaze, WASHLET+ S5 with contemporary design
  - **CT446CEFGNT40**  
Elongated bowl with CEFIONTECT
  - **ST448EMNA**  
Tank and cover only
  - **SW3446**  
WASHLET+ S5
  - **9AU321-A**  
WASHLET Adaptor

### OPTIONAL COMPONENTS

- **TSU48.10**  
10" Unifit Rough-In
- **TSU48.14**  
14" Unifit Rough-In
- **THU806#MBL-A**  
Trip Lever - Matte Black

### COLORS/FINISHES

- #01 Cotton



**DYNAMAX  
TORNADO FLUSH**



**EWATER+**



**CEFIONTECT**



**UNIVERSAL  
HEIGHT**

### PRODUCT SPECIFICATION

The two-piece, ultra high-efficiency, DYNAMAX TORNADO FLUSH toilet shall be dual flush 1.28 GPF/0.9 GPF. Toilet shall be coated with CEFIONTECT, elongated front bowl, high profile tank, UNIVERSAL HEIGHT, complete skirted bowl and chrome trip lever. Toilet shall be TOTO Model MW4483446CEMFGN#01.

**See SW3446 Specification Sheet for details on included WASHLET.**

### CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1, ASME A112.19.14
- Certifications: IAPMO(cUPC®), EPA WaterSense, State of Massachusetts, and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance, and others
- Complies with CA Prop 65 warning requirements



# MW4483446CEMFGN

## Aquia® IV Arc® WASHLET®+ S5 Two-Piece Toilet - 1.28 GPF/0.9 GPF

### SPECIFICATIONS


<b>Water Use</b>	1.28 GPF / 0.9 GPF (4.8 LPF / 3.4 LPF)
<b>Flush System</b>	DYNAMAX TORNADO FLUSH®
<b>Min. Water Pressure</b>	8 psi (Flowing)
<b>Water Surface</b>	7" x 5"
<b>Trap Diameter</b>	2-1/4"
<b>Rough-in</b>	12" (10" and 14" options available)
<b>Trap Seal</b>	2-1/8"
<b>Warranty</b>	One Year Limited Warranty
<b>Material</b>	Vitreous China
<b>Shipping Weight</b>	<b>CT446CEFGNT40:</b> 83 lbs <b>ST448EMNA:</b> 29 lbs <b>SW3446:</b> 15.4 lbs
<b>Shipping Dimensions</b>	<b>CT446CEFGNT40</b> 29-5/8" L x 16-3/8" W x 19-3/4" H <b>ST448EMNA</b> 20-1/2" L x 8-3/4" W x 17-1/2" H <b>SW3446</b> 24-3/8" L x 17-9/16" W x 7-7/16" H

See SW3446 Specification Sheet for details on included WASHLET.

### INSTALLATION NOTES


Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

### DIMENSIONS



**TOTO®**

These dimensions and specifications are subject to change without notice